

## asahi 44feet



Oil Pattern Distance 44 **Reverse Brush Drop** 44 Oil Per Board 50 ul **Forward Oil Total** 15.35 mL **Reverse Oil Total** 7.25 mL **Volume Oil Total** 22.6 mL **Tank Configuration Tank A Conditioner ICE Tank B Conditioner KGEGL A Only** 

	START	STOP	LOADS	MICS	SPEED	TANK	CROSSED	START	END	FEET	T.OIL
1	5L	5R	4	50	14	Α	124	0.0	5.9	5.9	6200
2	9L	9R	3	50	22	Α	69	5.9	15.2	9.3	3450
3	10L	10R	3	50	22	Α	63	15.2	24.5	9.3	3150
4	12L	12R	3	50	26	Α	51	24.5	35.5	11.0	2550
5	2L	2R	0	50	26	Α	0	35.5	38.0	2.5	0
6	2L	2R	0	50	30	Α	0	38.0	44.0	6.0	0

_											
	START	STOP	LOADS	MICS	SPEED	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	50	30	Α	0	44.0	25.0	-19.0	0
2	12L	12R	2	50	22	Α	34	25.0	18.8	-6.2	1700
3	11L	11R	2	50	22	Α	38	18.8	12.6	-6.2	1900
4	10L	10R	2	50	22	Α	42	12.6	6.4	-6.2	2100
5	5L	5R	1	50	18	Α	31	6.4	3.9	-2.5	1550
6	2L	2R	0	50	10	Α	0	3.9	0.0	-3.9	0

Cleaner Ratio Main Mix Cleaner Ratio Back End Mix Cleaner Ratio Back End Distance Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100

NA NA NA Forward Reverse Combined



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	MIddle: Inside	Middle: Inside Middle: Middle	
Track Zone Ratio	6.67	1.64	1	1	1.64	6.67



