



asahi 42feet 10月-12月




Oil Pattern Distance	42	Reverse Brush Drop	40	Oil Per Board	50 ul
Forward Oil Total	9.35 mL	Reverse Oil Total	11.1 mL	Volume Oil Total	20.45 mL
Tank Configuration	A Only	Tank A Conditioner	ICE	Tank B Conditioner	KGEGL

	START	STOP	LOADS	MICS	SPEED	TANK	CROSSED	START	END	FEET	T.OIL
1	5L	5R	2	50	14	A	62	0.0	1.9	1.9	3100
2	7L	7R	1	50	18	A	27	1.9	4.4	2.5	1350
3	10L	10R	2	50	22	A	42	4.4	10.6	6.2	2100
4	12L	12R	2	50	26	A	34	10.6	17.9	7.3	1700
5	15L	15R	2	50	30	A	22	17.9	26.4	8.5	1100
6	2L	2R	0	50	30	A	0	26.4	35.0	8.6	0
7	2L	2R	0	50	30	A	0	35.0	42.0	7.0	0

	START	STOP	LOADS	MICS	SPEED	TANK	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	50	30	A	0	42.0	40.0	-2.0	0
2	2L	2R	0	50	30	A	0	40.0	38.0	-2.0	0
3	15L	15R	2	50	26	A	22	38.0	30.7	-7.3	1100
4	13L	13R	2	50	26	A	30	30.7	23.4	-7.3	1500
5	12L	12R	2	50	22	A	34	23.4	17.2	-6.2	1700
6	11L	11R	1	50	22	A	19	17.2	14.1	-3.1	950
7	10L	10R	2	50	18	A	42	14.1	9.0	-5.1	2100
8	9L	9R	1	50	18	A	23	9.0	6.5	-2.5	1150
9	8L	8R	1	50	14	A	25	6.5	4.6	-1.9	1250
10	7L	7R	1	50	10	A	27	4.6	3.2	-1.4	1350
11	2L	2R	0	50	10	A	0	3.2	0.0	-3.2	0

Cleaner Ratio Main Mix NA Forward
Cleaner Ratio Back End Mix NA Reverse
Cleaner Ratio Back End Distance NA Combined
Buffer RPM: 4 = 700 | 3 = 500 | 2 = 200 | 1 = 100



Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside:Middle	Middle:Middle	Inside:Middle	Middle: Inside	Middle:Middle	Middle:Outside
Track Zone Ratio	13.13	2.23	1.08	1.08	2.23	13.13

